

CODE NUMBER

0325105

DESCRIPTION

Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, Electrical Override, Battery, Infrared, Exposed Sensor Urinal/Water Closet Retrofit Flushometer.

DETAILS

• Finish: Polished Chrome (CP)

• Power Type: Battery

Fixture Type: Urinal/Water ClosetFixture Connection: Top Spud

• Override: Electrical

FEATURES

• Indicator Lights - user in view and low battery

• Optional 24 hour sentinel flush



COMPLIANCES & CERTIFICATIONS











(ADA Compliant, BAA Compliant, BABAA Compliant, BREEAM Water Credit, Green Globes Water Credit)

ELECTRICAL SPECIFICATIONS

- Control Circuit: Solid State/6 VDC Input/24 Hour Sentinel Flush
- Sensor Range: 22"-42" (559-1,067mm)

VALVE OPERATING PRESSURE (FLOWING)

15–80 PSI (103–552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- Side Mount Operator Unit Installation Instructions
- Optima SMO Installation Instructions
- EBV-89A Side Mount Repair and Maintenance Guide
- Additional Downloads

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the EBV89A product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer. Find a compatible water closet for this flushometer.

WARRANTY

View Warranty Information

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



ROUGH-IN

Side Mount Operator unit shown on an existing Sloan Regal Model 110/111 Closet Flushometer

