

CODE NUMBER

10051423

DESCRIPTION

SU-1009 Urinal and REGAL 186 SFSM Flushometer.

COMPONENTS

- Flushometer: Code 3982530
- Urinal: Code 1101009

DETAILS

- Flush Volume: 0.5 gpf (1.9 Lpf)
- Nominal Dimensions: 14 $^{1}\!\!/_{4}" \times$ 17 $^{1}\!\!/_{4}" \times$ 25 $^{1}\!\!/_{2}"$ (362 \times 438 \times 648mm)

FLUSHOMETER FEATURES

- Four (4) size C batteries included
- "Low Battery" Flashing LED
- "User in View" Flashing LED
- No External Volume Adjustment to Ensure Water Conservation
- True Mechanical Override Flush Button
- 72-Hour Sentinel Flush
- Sweat Solder Adapter w/Cover Tube and Cast Wall Flange with Set Screw
- Stop Seat and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine resistance
- 3/4" I.P.S. Screwdriver Bak-Chek® Angle Stop with stop plug

FIXTURE FEATURES

- White Vitreous China
- Washdown flushing action
- Integral flushing rim
- ³/₄" I.P.S. top spud inlet
- 2" NPT outlet flange
- Vandal resistant strainer assembly included
- All mounting hardware included
- 100% factory flush tested



COMPLIANCES & CERTIFICATIONS



(ADA Compliant, BAA Compliant, BREEAM Materials Credit, BREEAM Water Credit, CalGreen Compliant, CEC Compliant, cUPC Certified, cUPC Green Certified (Requires use of listed vacuum breaker that complies with ASSE 1001), EPD, Green Globes Materials & Resources Credit, Green Globes Water Credit, HPD, LEED Materials & Resources EPD Credit, LEED Materials & Resources HPD Credit, LEED V4 Water Efficiency Credit, Satisfies LEED Credits, WaterSense Listed, WELL Building Standard)

DOWNLOADS

- EBV-500/550-A Installation Instructions
- Regal XL Exposed Installation Instructions
- EBV500/EBV550 Repair and Maintenance Guide
- Regal Flushometers Repair and Maintenance Guide
- SS/ST/SU/WETS/WEUS Fixtures Repair and Maintenance Guide
- Additional Downloads

NOTES


All information contained within this document subject to change without notice.


WARRANTY

View Warranty Information

SLOAN.

ROUGH-IN





3/4" IPS Supply (DN 20 mm) 4 3/4" (121 mm) |← 2 1/4" (57 mm) Centerline of Fixture 15 5/8" (397 mm) 11 1/2" (292 mm) Mounting Hole Center 串 -1 Ý 18° (457 mr 20 3/4" (527 mm) (Centerline of outlet) φ Ű Centerline of outlet to floc 19" (483 mm (12" for ADA) Centerline of outlet to floor 19" (483 mm) (12" for ADA) Δ (610 mm) (17" for ADA) é 17 1/4" (438 mm) --Finished Floor 1

> Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com