

CODE NUMBER

20101030

DESCRIPTION

ST-2010 Water Closet and ROYAL 940 Flushometer.

COMPONENTS

Flushometer: Code 3913407Water Closet: Code 2102010

DETAILS

• Flush Volume: 1.28 gpf (4.8 Lpf)

 \bullet Nominal Dimensions: 25 ½" \times 16 1/125" \times 15" (641 \times 407 \times

381mm)

FLUSHOMETER FEATURES

• ADA Compliant Non-Hold-Open Actuator

- Vacuum Breaker Flush Connection for 11/2" Back Inlet
- Non-Hold-Open Push Button, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation.
- Handle Packing, Main Seat, Stop Seat and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine resistance
- 1" I.P.S. Wheel Handle Bak-Chek® Angle Stop
- Includes HY100A Push Button Assembly

FIXTURE FEATURES

- White Vitreous China
- Elongated bowl
- Floor mounted, floor outlet
- Siphon jet flushing action achieves 1000g Map score
- Water spot area: 101/8" x 93/8" (26 cm x 24 cm)
- 1½ I.P.S. rear spud inlet
- 21/8" fully glazed trapway
- Closet bolts and caps included
- Toilet seat not included
- Static load rating of 1000 lbs. (See Notes)



COMPLIANCES & CERTIFICATIONS

















(BAA Compliant, BREEAM Water Credit, EPD, Green Globes Water Credit, HPD, LEED V4 Water Efficiency Credit, Satisfies LEED Credits, WaterSense Listed, WELL Building Standard)

DOWNLOADS

- Royal/Regal Series 900 Hydraulic Installation Instructions
- HET Rear Spud Installation Instructions
- SS/ST/SU/WETS/WEUS Fixtures Repair and Maintenance Guide
- Additional Downloads

NOTES

All information contained within this document subject to change without notice.


Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.


WARRANTY

View Warranty Information



ROUGH-IN





Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com