

### **CODE NUMBER**

22201435

### **DESCRIPTION**

### **COMPONENTS**

 Flushometer: Code 3080050 • Water Closet: Code 2102229

### **DETAILS**

• Flush Volume: 1.28 gpf (4.8 Lpf)

• Nominal Dimensions:  $26 \frac{3}{4}$ " × 14" ×  $16 \frac{1}{2}$ " (679 × 356 × 419mm)

## **FLUSHOMETER FEATURES**

- ADA Compliant Metal Oscillating Non-Hold-Open Handle
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Control Stop Plug
- Sweat Solder Adapter with Cover Tube
- Cast Wall Flange with Set Screw
- Vacuum Breaker Flush Connection
- Non-Hold-Open Handle and No External Volume Adjustment to **Ensure Water Conservation**

### **FIXTURE FEATURES**

- White Vitreous China
- Universal model works with Sloan flushometers from 1.1 to 1.6 gpf
- Elongated bowl
- Floor mounted, rear outlet
- Water spot area: 101/4" x 8" (26 cm x 24 cm)
- 1½" I.P.S. top spud inlet
- 21/8" fully glazed trapway
- Syphonjet flushing achieves up to 1000g Map Scores when used with Sloan flushometers
- Closet bolts and caps included
- Toilet seat not included



### **COMPLIANCES & CERTIFICATIONS**



























(ADA Compliant, BAA Compliant, BREEAM Materials Credit, BREEAM Water Credit, CalGreen Compliant, CEC Compliant, cUPC Certified, cUPC Certified (Requires use of listed vacuum breaker that complies with ASSE 1001), cUPC Green Certified, cUPC Green Certified (Requires use of listed vacuum breaker that complies with ASSE 1001), EPD, Green Globes Materials & Resources Credit, Green Globes Water Credit, HPD, LEED Materials & Resources EPD Credit, LEED Materials & Resources HPD Credit, LEED V4 Water Efficiency Credit, Satisfies LEED Credits, WaterSense Listed, WELL Building Standard)

### **DOWNLOADS**

- HET ST-2229 Series Installation Instructions
- Regal XL Exposed Installation Instructions
- EBV-500/550-A Installation Instructions
- Regal Flushometers Repair and Maintenance Guide
- SS/ST/SU/WETS/WEUS Fixtures Repair and Maintenance
- EBV500/EBV550 Repair and Maintenance Guide

### **NOTES**

All information contained within this document subject to change without notice.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.

# WARRANTY

View Warranty Information