

CODE NUMBER

3305201

DESCRIPTION

Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, True Mechanical Override, Hardwired, Exposed Sensor Hardwired Urinal/Water Closet Retrofit Flushometer.

DETAILS

Finish: Polished Chrome (CP)
Power Type: Hardwired
Battery Life: 3 years
Valve: Diaphragm

Valve Body Material: Semi-red Brass
 Fixture Type: Urinal/Water Closet
 Fixture Connection: Top Spud
 Override: True Mechanical (TMO)

FEATURES

- "User in View" Flashing LED
- Mechanical Manual Override Flush Handle
- 72 Hour Sentinel Flush Mode
- ADA Compliant OPTIMA® SMOOTH® Hardwire Powered Infrared Sensor for automatic "Hands-free" operation



COMPLIANCES & CERTIFICATIONS













(ADA Compliant, BREEAM Water Credit, cUPC Certified, UL Certified, CUL Certified, Green Globes Water Credit)

RECOMMENDED SPECIFICATION

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

ELECTRICAL SPECIFICATIONS

• Arming Delay: 8 seconds

• Battery Life: 3 years

Control Circuit: 6 VDC Input/72 Hour Sentinel Flush/Solid

• Sensor Range: 26"-32" (660-813mm)

• Transformers (specify separately):

EL-451 (up to 6 flushometers)

o EL-386 (Up to 1 flushometer)

VALVE OPERATING PRESSURE (FLOWING)

15–80 PSI (103–552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- EL 600-A Installation Instructions
- EL600A Smooth Side Mount Repair and Maintenance Guide
- Additional Downloads

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the EL600A product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer. Find a compatible water closet for this flushometer.



Battery life varies according to actual usage and restroom conditions.

WARRANTY

View Warranty Information

ROUGH-IN

