

#### **CODE NUMBER**

3315115BT

#### **DESCRIPTION**

Bluetooth, Trim Plate: None, Battery Power Supply, Back-Check Tee, Polished Chrome Finish, 0.5 gpm, Multi-Laminar Spray, Infrared Sensor, Optima® Battery or Turbine-Powered Deck-Mounted Low Integrated Base Body Faucet.

### **DETAILS**

• Flow Rate: 0.5 gpm (1.9 Lpm) (0.5GPM)

• Spray Type: Multi-Laminar (MLM)

Sensor Type: InfraredMounting Type: 4" Centerset

• Mounting Size: 4" Centerset, (3-hole) 1-1/4" to 1-1/2"

• Trim Plate: None

• Power Supply: Battery (BAT)

• Temperature Mixer: Back-Check Tee (TEE)

• Finish: Polished Chrome (CP)

Factory Default Timeout: 30 secondsFactory Default Gallons per Cycle: 0.25

#### **FEATURES**

ADA Compliant, Water Usage and Battery Strength Reporting, Wireless Settings Adjustment, Commercial Grade Faucet, Integrated Water Shut-off, Hygienic Line Flush, On-demand or Metered Activation, Self-adapting Sensor, Cast Brass Spout, Quick Connect Fittings

# **ELECTRICAL SPECIFICATIONS**

Battery Life: 3 years 8,000 cycles/month
 Optional power harvesting significantly extends service life

Sensor Range: 4"-5" (102-127mm)
Timeout Adjustment Settings: 30s

### **POWER SUPPLY OPTIONS**

- 6VDC Plug Adapter (sold separately), 0362006\*
- 6VDC Ganged Adapter Kit (up to 6 units)(sold separately), 0362035\*
- 24VAC Box Transformer (up to 3 units)(sold separately), 0345370PK\*
- Optional Turbine Energy Harvesting
- \* when converting units to hardwired with battery back-up

# **VIDEOS**

Sloan Connect App®


Sloan Optima Below Deck Faucet

PVD Special Finishes

# **DOWNLOADS**

- Optima Smart Faucet Below Deck Installation Instructions
- Faucet Spray Heads Repair and Maintenance Guide





### **COMPLIANCES & CERTIFICATIONS**



































(ADA Compliant, ASME A112.18.1 Compliant, CEC Compliant, cUPC Certified, cUPC Low Lead Compliant, EPD, GPC 0.25 or less, HPD, IAPMO, NSF-61, NYC604.4, Proposition 65, TAS, UPC Certified, UPC Low Lead Compliant, WaterSense Listed, WELL Building Standard)

# RECOMMENDED SPECIFICATION

Faucet shall include cast brass body, quick-connect fittings, twist-off/shut-off solenoid assembly, removable battery cartridge, flexible power supply and allow adjustment of settings wirelessly via Apple or Android smartphones.

#### **NOTES**

All information contained within this document subject to change without notice.

Looking for other variations of the EBF-650 product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet.

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



# OPTIMA® SENSOR FAUCET EBF-650-BAT-TEE-CP-0.5GPM-MLM-LL-FCT

**Discontinued** 

- ETF-600/EBF-650 Below Deck Repair and Maintenance Guide
- Trim Plate Guide
- Additional Downloads

Find a compatible sink for this faucet.

### WARRANTY

View Warranty Information



#### **ROUGH-IN**

