

CODE NUMBER

3315421BT

DESCRIPTION

Bluetooth, Trim Plate: None, Battery Power Supply, Below Deck Thermostatic Mixing Valve, Polished Chrome Finish, 0.35 gpm, Multi-Laminar Spray, Infrared Sensor, Optima® Battery or Turbine-Powered Deck-Mounted Mid Body.

DETAILS

• Flow Rate: 0.35 gpm (1.3 Lpm) (0.35GPM)

• Spray Type: Multi-Laminar (MLM)

 Sensor Type: Infrared • Mounting Type: Single Hole

• Mounting Size: Single Hole 1-3/16"

• Trim Plate: None

• Power Supply: Battery (BAT)

• Temperature Mixer: Below Deck Thermostatic Mixing Valve (BDT)

• Finish: Polished Chrome (CP)

• Factory Default Timeout: 30 seconds • Factory Default Gallons per Cycle: 0.25

FEATURES

ADA Compliant, Water Usage and Battery Strength Reporting, Wireless Settings Adjustment, Commercial Grade Faucet, Integrated Water Shut-off, Hygienic Line Flush, On-demand or Metered Activation, Self-adapting Sensor, Cast Brass Spout, Quick Connect **Fittings**

ELECTRICAL SPECIFICATIONS

• Battery Life: 3 years 8,000 cycles/month Optional power harvesting significantly extends service life

• Sensor Range: 4"-5" (102-127mm) • Timeout Adjustment Settings: 30s

POWER SUPPLY OPTIONS

6VDC Plug Adapter (sold separately), 0362006*

* when converting units to hardwired with battery back-up

VIDEOS

Sloan Optima Below Deck Faucet

PVD Special Finishes

Sloan Connect App®


• Optima Smart Faucet Below Deck Installation Instructions

- Faucet Spray Heads Repair and Maintenance Guide
- Optima EBF-425 / ETF-420 Repair & Maintenance Guide and Parts Breakdown
- Trim Plate Guide

DOWNLOADS

Additional Downloads





COMPLIANCES & CERTIFICATIONS



(ADA Compliant, ASME A112.18.1 Compliant, ASSE 1070, BREEAM Materials Credit, BREEAM Water Credit, CalGreen Compliant, CEC Compliant, cUPC Certified, UPC Certified, UPC Low Lead Compliant, cUPC Low Lead Compliant, EPD, Green Globes Materials & Resources Credit, Green Globes Water Credit, HPD, IAPMO, LEED Materials & Resources EPD Credit. LEED Materials & Resources HPD Credit, WaterSense Listed, NSF-61, NYC604.4, Proposition 65, Satisfies LEED Credits, TAS, WELL Building Standard)

RECOMMENDED SPECIFICATION

Faucet shall include cast brass body, quick-connect fittings, twist-off/shut-off solenoid assembly, removable battery cartridge, flexible power supply and allow adjustment of

Sloan 10500 Seymour Ave, Franklin Park, IL 60131



settings wirelessly via Apple or Android smartphones.

NOTES

All information contained within this document subject to change without notice.


Looking for other variations of the EBF-425 product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.

WARRANTY

View Warranty Information

ROUGH-IN



Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com