

#### **CODE NUMBER**

33250026

## **DESCRIPTION**

PWT™ Concealed Solenoid (less sensor) Water Closet PWT Flushometer.

#### **DETAILS**

• Flush Volume: 1.6/2.4/3.5 gpf (6.0/9.1/13.2 Lpf)

Finish: Rough BrassPower Type: BatteryValve: Diaphragm

Fixture Type: Water ClosetProgram: A4 (PRGM-A4)

• Push Button: Metal Button Fixture Wall Actuator (MBFW)

#### **FEATURES**

- Program set to 2 activations in 5 minutes with 15 minutes lockout
- Program is field changeable to 30, 45 and 60 minute lockout times, or dorm setting
- Can be used with stainless-steel water closet fixtures from Acorn®, Bradley®, Metcraft® and other manufacturers
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- 1.6, 2.4 and 3.5 gpf options
- Single Flush
- Solenoid operated
- Includes touch button
- Stainless steel, vandal proof button, chemical resistant push-button operation designed with non-hold-open feature to keep fixture from surpassing intended water consumption
- Connector cable has white arrows for easy alignment
- Battery powered
- Four (4) Size AA Battery Power source
- Low Battery flashing LED
- Conversion Kit for Manual flushometers:
- Royal 603
- Royal 611
- Royal 613
- Conversion Kit for Hydraulic flushometers:
- Royal 9603
- Royal 9611
- Royal 9613



## **COMPLIANCES & CERTIFICATIONS**











(ADA Compliant, BAA Compliant, cUPC Certified, UL Certified, UPC Certified)

#### RECOMMENDED SPECIFICATION

Valve shall be in compliance to the applicable sections of ASSE 1037.

## **VALVE OPERATING PRESSURE (FLOWING)**

15–80 PSI (103–552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

# **DOWNLOADS**

- 8603-ESM Retrofit Installation Instructions
- 8603-ESM Maintenance Guide
- Control Stop Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Additional Downloads

### NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the PWT-ESM RESS product? View the general spec sheet with all options.

## WARRANTY

**View Warranty Information**