

CODE NUMBER

3365209BT

DESCRIPTION

Bluetooth, 8" Trim Plate, Box Transformer Power Supply, Above Deck Mixer, Polished Chrome Finish, 1.5 gpm, Shower Head Spray, Infrared Sensor, Optima® Hardwired-Powered Deck-Mounted Gooseneck Body Faucet.

DETAILS

• Flow Rate: 1.5 gpm (5.7 Lpm) (1.5GPM)

• Spray Type: Shower Head (SHR)

• Spout Type: Surgical Bend (S)

Sensor Type: Infrared

• Mounting Type: 8" Centerset

• Mounting Size: Single Hole 1-1/4" to 1-1/2"

• Trim Plate: 8" (203mm) (8)

Power Supply: Box Transformer (BOX)

• Temperature Mixer: Above Deck Mixer (ADM)

• Finish: Polished Chrome (CP)

• Factory Default Timeout: 30 seconds

• Factory Default Gallons per Cycle: 0.75

FEATURES

ADA Compliant, Water Usage and Battery Strength Reporting, Wireless Settings Adjustment, Commercial Grade Faucet, Integrated Water Shut-off, Hygienic Line Flush, On-demand or Metered Activation, Self-adapting Sensor, Cast Brass Spout, Quick Connect Fittings

ELECTRICAL SPECIFICATIONS

• Battery Life: 3 years 8,000 cycles/month

Optional power harvesting significantly extends service life

• Sensor Range: 8"-10" (203-254mm)

• Timeout Adjustment Settings: 30s

POWER SUPPLY OPTIONS

• 6VDC Plug Adapter (included with PLG models), 0362006

 6VDC Ganged Adapter Kit (up to 6 units)(sold separately), 0362035*

• 24VAC Box Transformer (included with BOX models), 0345370PK

* when converting units to hardwired with battery back-up

VIDEOS

Sloan Connect App®

Sloan Optima Below Deck Faucet

DOWNLOADS


• Optima Smart Faucet Below Deck Installation Instructions

• Trim Plate Guide

• Faucet Spray Heads Repair and Maintenance Guide

• ETF-700/700-S and EBF-750/750-S Below Deck Repair and Maintenance Guide





COMPLIANCES & CERTIFICATIONS



ASMI

























(ADA Compliant, ASME A112.18.1 Compliant, CEC Compliant, cUPC Certified, cUPC Low Lead Compliant, EPD, HPD, IAPMO, NSF-61, Proposition 65, TAS, UL Certified, UPC Certified, UPC Low Lead Compliant, WaterSense Listed, WELL Building Standard)

RECOMMENDED SPECIFICATION

Faucet shall include cast brass body, quick-connect fittings, twist-off/shut-off solenoid assembly, removable battery

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com





• Additional Downloads

cartridge, flexible power supply and allow adjustment of settings wirelessly via Apple or Android smartphones.

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the ETF-700 product? View the general spec sheet with all options.


Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.


WARRANTY


View Warranty Information



ROUGH-IN







Double Inlet Filter Fitting

Single Inlet Filter Fitting Kit with Below Deck Manual Mixing Valve (BDM)

Single Inlet Filter Fitting Kit with Below Deck Thermostatic Mixing Valve (BDT)

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com