

CODE NUMBER

3375424

DESCRIPTION

0.5 gpf, Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, Electrical Override, Battery, Infrared, ECOS® Exposed Sensor Urinal Retrofit Flushometer.

DETAILS

Flush Volume: 0.5 gpf (1.9 Lpf)
Finish: Polished Chrome (CP)
Power Type: Battery

Power Type: BatteValve: Diaphragm

• Valve Body Material: Semi-red Brass

• Fixture Type: Urinal

• Fixture Connection: Top Spud

• Override: Electrical

FEATURES

- Valve shall be in compliance to the applicable sections of ASSE 1037.
- Chrome plated metal handle cap



COMPLIANCES & CERTIFICATIONS











(ADA Compliant, BREEAM Water Credit, cUPC Certified, cUPC Green Certified, Green Globes Water Credit, Satisfies LEED Credits)

RECOMMENDED SPECIFICATION

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

ELECTRICAL SPECIFICATIONS

• Arming Delay: 8 seconds

• Flush Delay: 1s

• Self-Adaptive Window: ±8

• Sensor Range: 15"-30" (381-762mm)

VALVE OPERATING PRESSURE (FLOWING)

15-80 PSI (103-552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- Sloan ECOS Single/Dual-Flush Flushometer & Retrofit Valve Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- ECOS Repair and Maintenance Guide
- ECOS HW Repair and Maintenance Guide
- Additional Downloads

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the ECOS RESS-U product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer.



Find a compatible water closet for this flushometer.

WARRANTY

View Warranty Information

ROUGH-IN



