

CODE NUMBER

34000007

DESCRIPTION


1.6/2.4/3.5 gpf, Filtered, Polished Brass Finish, Fixture Connection
Rear Spud, Dual Flush, TruFlush Concealed Manual Water Closet
Flushometer.

DETAILS

- Flush Volume: 1.6/2.4/3.5 gpf (6.0/9.1/13.2 Lpf)
- Finish: Polished Brass (PB)
- Bypass: Filtered
- Fixture Type: Water Closet
- Fixture Connection: Rear Spud

FEATURES

- True flushometer provides accurate flush volume
- Heavy-duty rough brass valve body
- Vandal-resistant wall plate with easy to push button
- Replaceable piston assembly accessible through front wall plate
- Concealed shut off sleeve adjusts flow rate
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass

**COMPLIANCES & CERTIFICATIONS**

(UPC Certified)

RECOMMENDED SPECIFICATION

Valve shall be concealed with front access wall plate smaller than 7" x 7" and shall have integrated control stop. Valve shall be in compliance with ASTM Alloy Classification for Semi-Red Brass.

VALVE OPERATING PRESSURE (FLOWING)

20-80 PSI (138-552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- [TRF-1036-N, 1024-N Manual Dual Flush India Installation Instructions - India](#)
- [TRF-1000 Manual Dual Flush Wall Plate Installation Instructions - India](#)
- [TRF-1036-N, 1024-N Manual Dual Flush Valve Repair and Maintenance Guide - India](#)

NOTES

All information contained within this document subject to change without notice.

WARRANTY

[View Warranty Information](#)