

CODE NUMBER

80298013

DESCRIPTION

Floor-Mounted 1.6 gpf (6.0 Lpf) ADA 12" Rough-in Left Handle Pressure-Assisted/Tank Toilet.

COMPONENTS

Bowl: Code 2108029Tank: Code 2108013

DETAILS

• Flush Volume: 1.6 gpf (6.0 Lpf)

• Handle Side: Left

FEATURES

- White Vitreous China
- Elongated bowl
- Floor mounted, floor outlet
- 12" (305mm) rough-in
- Chrome metal flush handle
- Secure, anti-rocking 3-point tank mounting system
- Powered by Flushmate® brand pressure assisted flushing technology to achieve 1,000g MaP score
- Over 60 ft (18.3 m) drainline carry performance
- Water spot area: 11 ½ x 9¾ (286 mm x 248 mm)
- Smooth, quiet cable activated flush handle left hand
- Fully glazed trapway
- Closet bolts and caps included
- Toilet seat and wax ring not included
- Tank and bowl are packed in a single carton

PLUMBING SYSTEM REQUIREMENTS

Maximum Static Pressure: 80 PSI (552 kPa)
Minimum Static Pressure: 20 PSI (138 kPa)

• Millimum Static Flessure. 20 FSI (130 KF

DOWNLOADS

- Pressure-Assisted Toilets Installation Instructions
- Flushmate Owner's Manual
- Pressure-Assisted Toilets Repair and Maintenance Guide
- Additional Downloads



COMPLIANCES & CERTIFICATIONS









(ADA Compliant, BAA Compliant, cUPC Certified, cUPC Green Certified)

NOTES

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

All information contained within this document subject to change without notice.

WARRANTY

View Warranty Information

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



ROUGH-IN

